

MODEL	MAIN TANK (L)	ELEVATOR MAX LOAD (KG) (6 BAR)	PLATFORM LIFT	MAX STATIC LOAD** (KG)	ULTRASOUND POWER (KW)	HEATING POWER (KW)	MAIN TANK INTERNAL MEASURES (MM)	PLATFORM TRAY DIMMENSION (MM)	USEFUL HEIGHT (MM)	EXTERNAL MEASURES WITH TOP LID OPEN (MM)	OIL SEPARATOR LFS	AUTOMATIC TOP LID OPENING
ACM-100	113	50	Pneumatic	100	1	3,75	600 x 400 x 470	550 x 320	345	1.070 x 720 x 1.335	YES	NO
ACM-200	200	75	Pneumatic	150	2	7,5	800 x 500 x 500	750 x 420	375	1.270 x 825 x 1.420	YES	NO
ACM-350	403	250	Pneumatic	470	3	7,5	1.000 x 650 x 620	950 x 527	450	1.807 x 1.204 x 1.740	YES	OPTIONAL
ACM-500	587	350	Pneumatic	700	4	11	1.200 x 670 x 730	1.090 x 544	530	2.050 x 1.220 x 1.856	YES	OPTIONAL
ACM-750	840	500	Pneumatic	1.000	5	11	1.400 x 800 x 750	1280 x 670	550	2.170 x 1.360 x 1.880	YES	OPTIONAL
ACM-1000	1.224	800	Pneumatic	1.600	7	18	1.600 x 900 x 850	1480 x 760	650	2.375 x 1.495 x 2.095	YES	YES
ACM-2000	2.178	1.000	Hydraulic	2.000	9	27	1.800 x 1.100 x 1.100	1.750 x 900	900	2.450 x 1.600 x 2.400	YES	YES
ACM-3000	3.276	1.000	Hydraulic	2.000	12	27	2.100 x 1.300 x 1.200	2.050 x 1.110	1000	2.750 x 1.800 x 3.000	YES	YES
ACM-4500	4.846	1.800	Hydraulic	3.600	15	36	2.400 x 1.590 x 1.270	2.350 x 1.400	1020	3.085 x 2.150 x 3.300	YES	YES
ACM-5500	6.010	1.800	Hydraulic	5.000	18	45	2.700 x 1.590 x 1.400	2.650 x 1.400	1150	3.385 x 2.150 x 3.450	YES	YES
ICM-8000	9.184			7.000	27	54	3.200 x 2.050 x 1.400		1200	3.520 x 2.750 x 4.350	YES	YES
ICM-12000	13.260			12.000	36	72	4.600 x 1.950 x 1.460		1260	6.190 x 2.890 x 4.400	YES	YES

*All ACM models available also in ICM execution, without the platform lift

**ICM model maximum load or ACM model with platform lift static on the lowest position

To get the best cleaning performance parts should be separated from each other and from the tank walls at least 100 mm.